



## Fabric Specification: 2537 Auster

Fabric type: Panel

### Construction Specifications

Fiber Contents:		100% recycled polyester
Yarns:	Warp:	Filament
	Fill:	Filament and woolen spun
Ends/inch:		138+/-4
Picks/inch:		54+/-2
Weave type:		Jacquard
Repeat:	Horizontal:	13.9"
	Vertical:	16"
Width:		66" min. usable
Weight:		11.4+/-1.0 oz/lin yd
Chemical finish/coatings:		None

### Performance Specifications

Colorfastness to Light:  
(AATCC 16 Option 3) Class 4 min. at 40 hr.

Colorfastness to Crocking:  
(AATCC 8) Class 4 min. Dry  
Class 3 min. Wet

Breaking Strength: (ASTM D5034)	Warp	250 lbf min.
	Fill	140 lbf min.

Tear Strength: (ASTM D2261)	Warp	20 lbf min.
	Fill	20 lbf min.

### Flammability

ASTM E84 Class A or 1

Cleaning Code WS

TES-2537 Rev B

Effective date: March 1, 2005

Approval: Alan Dean

Page 1 of 1

5300 Corporate Grove Drive SE, Suite 250 Grand Rapids, MI 49512

Phone: 800.544.0200 Fax: 616.554.2255

Printed copies are uncontrolled unless stamped "Controlled" in red. See [www.true textiles.com](http://www.true textiles.com) for most recent revision.