



## Fabric Specification: 2671 Sprite

**Fabric type:** Panel

### Construction Specifications

**Fiber Contents:** 95% post-industrial recycled polyester  
5% post-consumer recycled polyester

<b>Yarns:</b>	<b>Warp:</b>	Filament
	<b>Fill:</b>	Filament and spun
<b>Ends/inch:</b>		53 +/-2
<b>Picks/inch:</b>		24 +/-2
<b>Weave type:</b>		Dobby
<b>Width:</b>		66" min. usable
<b>Weight:</b>		10.8 +/- 0.5 oz/lin yd
<b>Repeat:</b>	<b>Horizontal</b>	0.26"
	<b>Vertical</b>	0.83"
<b>Chemical finish/coatings:</b>		Polyester binder

### Performance Specifications

**Colorfastness to Light:** (AATCC 16 Option 3) Class 4 min. at 40 hr.

**Colorfastness to Crocking:** (AATCC 8) Class 4 min. Dry  
Class 3 min. Wet

<b>Breaking Strength:</b> (ASTM D5034)	<b>Warp</b>	175 lbf min.
	<b>Fill</b>	175 lbf min.

<b>Tear Strength:</b> (ASTM D2261)	<b>Warp</b>	35 lbf min.
	<b>Fill</b>	25 lbf min.

### Flammability

ASTM E84 Class A or 1

**Cleaning Code** WS

TES-2671 Rev A  
Effective date: January 5, 2009  
Approval: Alan Dean

Page 1 of 1

5300 Corporate Grove Drive SE, Suite 250 Grand Rapids, MI 49512  
Phone: 800.544.0200 Fax: 616.554.2255

Printed copies are uncontrolled unless stamped "Controlled" in red. See [www.true textiles.com](http://www.true textiles.com) for most recent revision.