



## Fabric Specification: 2701 Route 66

**Fabric type:** Panel

### Construction Specifications

Fiber Contents:		50% post-industrial recycled polyester 20% post-consumer recycled polyester 30% polypropylene
Yarns:	Warp:	Filament
	Fill:	Filament and spun
Ends/inch:		74 +/-2
Picks/inch:		29 +/-2
Weave type:		Jacquard
Width:		66" min. usable
Weight:		13.9 +/- 1.0 oz/lin yd
Repeat:	Horizontal	Not applicable
	Vertical	Not applicable
Chemical finish/coatings:		None

### Performance Specifications

Colorfastness to Light:  
(AATCC 16 Option 3) Class 4 min. at 40 hr.

Colorfastness to Crocking:  
(AATCC 8) Class 4 min. Dry  
Class 3 min. Wet

Breaking Strength:  
(ASTM D5034) Warp 250 lbf min.  
Fill 150 lbf min.

Tear Strength:  
(ASTM D2261) Warp 40 lbf min.  
Fill 30 lbf min.

### Flammability

ASTM E84 Class A or 1

**Cleaning Code** WS

TES-2701 Rev A

Effective date: January 5, 2009

Approval: Alan Dean

Page 1 of 1

5300 Corporate Grove Drive SE, Suite 250 Grand Rapids, MI 49512

Phone: 800.544.0200 Fax: 616.554.2255

Printed copies are uncontrolled unless stamped "Controlled" in red. See [www.truetextiles.com](http://www.truetextiles.com) for most recent revision.