



Fabric Specification: 3495 Coastline

Fabric type: Panel

Construction Specifications

Fiber Contents:		66% pre-consumer recycled polyester 34% post-consumer recycled polyester
Yarns:	Warp:	Filament
	Fill:	Woolen spun and filament
Ends/inch:		73+/-2
Picks/inch:		41+/-2
Weave type:		Jacquard
Width:		66" min. usable
Weight:		12.2+/-1.0 oz/lin. yd
Repeat:	Horizontal	16.6"
	Vertical	16"
Chemical finish/coatings:		None

Performance Specifications

Colorfastness to Light:
(AATCC 16 Option 3) Class 4 min. at 40 hr.

Colorfastness to Crocking:
(AATCC 8) Class 4 min. Dry
Class 3 min. Wet

Breaking Strength: (ASTM D5034)	Warp	220 lbf min.
	Fill	100 lbf min.

Tear Strength: (ASTM D2261)	Warp	25 lbf min.
	Fill	18 lbf min.

Flammability

ASTM E-84 Class 1 or A

Cleaning Code WS

TES-3495 Rev B
Effective date: July 8, 2009
Approval: Alan Dean

Page 1 of 1

5300 Corporate Grove Drive SE, Suite 250 Grand Rapids, MI 49512
Phone: 800.544.0200 Fax: 616.554.2255

Printed copies are uncontrolled unless stamped "Controlled" in red. See www.truetextiles.com for most recent revision.