



Fabric Specification: 3575 Venezia

Fabric type: Panel

Construction Specifications

Fiber Contents:		57% pre-consumer recycled polyester 43% polyester
Yarns:	Warp:	Filament
	Fill:	Open End Spun
Ends/inch:		72+/-2
Picks/inch:		28+/-2
Weave type:		Jacquard
Width:		66" min. usable
Weight:		12.0+/-1.0 oz/lin yd
Chemical finish/coatings:		None

Performance Specifications

Colorfastness to Light: (AATCC 16 Option 3)		Class 4 min. at 40 hr.
--	--	------------------------

Colorfastness to Crocking: (AATCC 8)		Class 4 min. Dry Class 3 min. Wet
---	--	--------------------------------------

Breaking Strength: (ASTM D5034)	Warp	125 lbf min.
	Fill	75 lbf min.

Tear Strength: (ASTM D2261)	Warp	15 lbf min.
	Fill	15 lbf min.

Flammability

ASTM E84 CA Technical Bulletin 117 Sec. E		Class A or 1 Passes
--	--	------------------------

Cleaning Code		WS
---------------	--	----

TES-3575 Rev C
Effective date: January 19, 2009
Approval: Alan Dean

Page 1 of 1

5300 Corporate Grove Drive SE, Suite 250 Grand Rapids, MI 49512
Phone: 800.544.0200 Fax: 616.554.2255

Printed copies are uncontrolled unless stamped "Controlled" in red. See www.true textiles.com for most recent revision.