



Fabric Specification: 4052 Belgrade

Fabric type: Panel

Construction Specifications

Fiber Contents:		95% post-consumer recycled polyester 5% pre-consumer recycled polyester
Yarns:	Warp:	Wrap spun
	Fill:	Wrap spun
Ends/inch:		18+/-1
Picks/inch:		18+/-1
Weave type:		Crepe
Width:		66" min. usable
Weight:		18.5+/-1.0 oz/lin. yd
Repeat:	Horizontal	Not applicable
	Vertical	Not applicable
Chemical finish/coatings:		None

Performance Specifications

Colorfastness to Light:
(AATCC 16 Option 3) Class 4 min. at 40 hr.

Colorfastness to Crocking:
(AATCC 8) Class 4 min. Dry
Class 3 min. Wet

Breaking Strength: (ASTM D5034)	Warp	175 lbf min.
	Fill	175 lbf min.

Tear Strength: (ASTM D2261)	Warp	50 lbf min.
	Fill	50 lbf min.

Flammability

ASTM E-84 Class 1 or A

Cleaning Code WS

TES-4052 Rev F

Effective date: October 5, 2009

Approval: Alan Dean

Page 1 of 1

5300 Corporate Grove Drive SE, Suite 250 Grand Rapids, MI 49512

Phone: 800.544.0200 Fax: 616.554.2255

Printed copies are uncontrolled unless stamped "Controlled" in red. See www.true textiles.com for most recent revision.