



Soft-Tone® Acoustical/Tackable Wall & Ceiling Panels

A versatile sound barrier which has acoustical qualities, and tackability.

Lamvin's standard panel construction:

Fabric Color selector:
[\[click here to open in pdf format\]](#)

Acoustical Core:
 Perforated mineral fiberboard

Tackable Core :
 Non-perforated mineral fiberboard

Finish:
Acoustical: Vinyls are type II 18%, or micro perforated.
Fabrics: Acoustically transparent 100% woven polyester, 66 inches wide, 2-ply, 16 ounce fabric. The fabric is bonded directly to the panel face with all edges wrapped a minimum of 1-1/2 inches to the back of the panel to ensure a flat, wrinkle-free surface with tailored corners. Specified and other fabrics and perforated vinyls are available.



Tackable: Non-perforated vinyls are type II

Fabrics: (standard as shown above)

Size and thickness:

Thickness		
Soft-Tone 50 Series	1/2" STC 24	NRC 50
Soft-Tone 60 Series	3/4" STC 26	NRC 60
Soft-Tone 80 Series	1" STC 26	NRC 80
Width:	Up to 48"	
Height:	Up to 120"	

Edge details available:



Tackable panel

Fire test:
 ASTM E 84 / Class I (or A) flame spread rating (tunnel test)

Mountings available:
 Adhesive, concealed spline, edge clip, Velcro

Lamvin, Inc.

4675 North Avenue, Oceanside, CA 92056 - (800) 446 - 6329 & (760) 806 - 6400