



## Standard Acoustical Wall & Ceiling Panels

Economical and Lightweight

### Lamvin's standard panel construction:

Fabric Color selector:

[[click here to open in pdf format](#)]

Acoustical Core:

6-7lb. density, rigid fiberglass

Edges:

Chemically hardened edges to reinforce panel perimeter against warping and damage (aluminum edge available).

Finish:

Acoustically transparent 100% woven polyester, 66 inches wide, 2-ply, 16 ounce fabric. Fabric is bonded directly to the panel face with all edges wrapped a minimum of 1-1/2 inches to the back of the panel to ensure a flat, wrinkle-free surface with tailored corners. Specified and other fabrics and perforated vinyls are available.

Size and thickness:

Thickness	1/2", 3/4", 1", 1-1/2", 2", 3", 4" (Custom thickness available)
Width	Up to 48"
Height	Up to 120"
Additional	1" substrate also available 60" x 120" and 48" x 144"

Edge details available:



Bevel



Mitered



Tegular



Radius




Pencil Radius



Square



**NRC 0.85 to 0.95 on 1"**  
**NRC 1.00 to 1.10 on 2"**



Fire test:

**ASTM E 84**  
Class I (or A) flame spread  
rating (tunnel test)  
**UBC Standard 8-2**  
(corner burn test)

Mountings available:

Velcro  
Adhesive  
Impaling clip  
Concealed spline  
Mechanical "Z" clip  
Rotofast clip

Lamvin, Inc.

4675 North Avenue, Oceanside, CA 92056 - (800) 446 - 6329 & (760) 806 - 6400